

Hog Ring Plier Type HR 62-CL20

The BeA Hog Ring Plier HR 62-CL20 takes flexible hog ring staples type CL 20 x 1,6. For reaching tight areas, the tool is fitted with an extended nose. The rear loading magazine allows easy and quick reloading. This is a versatile tool for many different applications.



Popular applications:

Mattresses, automotive seating, bedding, wire cages, fencing, other wire connections, etc.

Length: 230 mm
Width: 110 mm
Height: 390 mm

Technical data

Type description:	HR 62-CL20 Standard
Article code:	12100136
Magazine type :	Rear loader
Safety:	-
Fastener type:	CL 20
Magazine capacity:	140
Fasteners per strip:	2 x 70
Operating pressure:	4 – 7 bar
Max. operating pressure:	8.3 bar
Air consumption/operation:	1.0 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 80 dB
Weight:	1.55 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the stapler: Operating instructions, spare parts list, service instructions

Subject to technical modifications.

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Product leaflet HR 62-CL20


Hog Ring Plier Type HR 62-CL20

Staples type CL 20



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	W = Width mm
CL 20 x 1.6 NK Flex	20

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut