

Pneumatic Bradder Type SK 355-222

The light weight bradder (1.3 kg) drives brad nails type SK 300 in the length of 15 to 55 mm. The non-mar rubber tip prevents scratches. The slim nose and rear-cut magazine allows reaching tight spots. The lock-out mechanism prevents the tool from operating unless brad nails are loaded in the magazine. The indicator signifies reloading timing through its transparent magazine-side. The bradder is equipped with an adjustment for depth control and an adjustable exhaust deflector.



Popular applications:

Door and window casings, sub flooring, cabinet assembly, case back nailing, plywood, decorative boards and other interior finish works, etc.

Length: 246 mm
Width: 60 mm
Height: 243 mm

Technical data

Type description:	SK 355-222 Standard
Article code:	12100205
Magazine type :	Side loader
Safety:	Single actuation
Fastener type:	Brads SK 300
Magazine capacity:	100
Fasteners per strip:	2 x 50 / 1 x 100
Operating pressure:	4 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0.5 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d = 82 dB
Single-shot sound pressure level:	L WA, 1 s,d = 91 dB
Weight:	1.3 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 3.3 m/s².

Extras supplied with the bradder: Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Bradder Type SK 355-222

Brads type SK 300



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0)4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
SK 315 NK	15
SK 320 NK	20
SK 325 NK	25
SK 330 NK	30
SK 335 NK	35
SK 340 NK	40
SK 345 NK	45
SK 350 NK	50

Other colours are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut