

## Pneumatic Nailer Type W 15-760

The light and well balanced nailer drives corrugated fasteners type W in lengths from 9 to 15 mm. It satisfied a multitude of fastening requirements and is the perfect solution when fastening butt and corner joints.



### Popular applications:

Butt and corner jointing in furniture, windows and doors.

Length: 382 mm  
Width: 70 mm  
Height: 260 mm

### Technical data

Type description:	<b>W 15 - 760</b>
Article code:	12200071
Magazine type :	Top loader
Safety:	Contact actuation
Fastener type:	Corrugated Fasteners Type W
Magazine capacity:	77
Fasteners per strip:	3x 24
Operating pressure:	6 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	1.5 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 90 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 97 dB
Weight:	2.53 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 3.3 m/s<sup>2</sup>.

<b>Extras supplied with the nailer:</b>	Operating instructions, spare parts list, service instructions, silencer
---	--

Subject to technical modifications.

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)

Product leaflet W 15-760


## Pneumatic Tacker Type W 15-760

Corrugated fasteners Type W



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: +49 (0) 4102 78-0  
Fax: +49 (0)4102 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



Description	L = Length mm
W 09 BK A	09
W 12 BK A	12
W 15 BK A	15

**Explanations:**

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut