



New – the lightest tool for staples type 180 in the market and also a power pack!



BeA Stapler 180/65-835C

- With only 2,7 kg the lightest tool in the market for staples type 180
- Extreme powerful
- Quickest shot sequence
- New ergonomic operator friendly handgrip
- Adjustable exhaust
- Adjustment for depth control
- New back nose assembly for faster loading
- Service friendly quick release
- Special formed nose for precise working
- Available with contact actuation and with single actuation
- To use for all staples type 180 from 40 - 65 mm (VZ HZ, NR HZ, NK HZ) and Q 180



Applications

Prefabricated house building, framing, roofing, flooring, truss building etc.

BeA 180/65-835C

Technical Data




Type description	180/65-835C Standard
Article code	12000500
Magazine type	Top loader
Safety	Contact actuation*
Fastener type	Type 180
Magazine type	Min. 157 staples
Fasteners per strip	2 x 60 (VZHZ = 3 x 40)
Operating pressure	6 - 8 bar
Max operating pressure	8 bar
Air consumption /operation	2,9 litre / 6 bar
Inner hose diameter	Ø 9 - 10 mm LW recommended
Emmision sound pressure level at the workstation	L pA, 1s, d= 82 dB
Single-shot emmision sound pressure level	L pA, 1s, d= 89 dB
Weight	2.70 kg
The vibration as per ISO 8662-1 1 is 3,2 m/s ² .	
Extras supplied with the nailer	Operating instructions, spare part list, serviceinstructions, silencer

Subject to technical modifications

*Also available with single actuation set: art. No. 14408803

Staples Type 180



Description	L = Length mm
180/40 NK HZ	40
180/45 NK HZ	45
180/50 NK HZ	50
180/55 NK HZ	55
180/60 NK HZ	60
180/63 NK HZ	63
180/65 NK HZ	65

Joh. Friedrich Behrens AG
Industrial Fastening Systems
Bogenstraße 43 - 45
22926 Ahrensburg
Germany

Further information:
Phone: +49 (0) 41 02 78 - 444
Fax +49 (0) 41 02 78 - 270
eMail: info@bea-group.com
www.Bea-Group.com

Staples type 180 are available in VZ HZ + NR HZ and are certified to DIN 1052.

BeA is a member of following associations:

