



BeA Hotmelt Applicator BeA 315

For hotmelt adhesive sticks Ø 43 mm

- Automatic temperature adjustment
- Very user friendly handling
- High security level due to stand-by function
- Electronic error indicator

Applications

Furniture and textile industry, upholstery applications



BeA 315

Technical specifications




Description	BeA 315
Art No.	12500186
EAN-Code	4045759056397
Voltage / power consumption	230 V / 400 W
Melting rate	3,8 kg / 8 1/4 lbs / hour
Temperatur control	Electronic, exchangeable temperatur modules
Feed mechanism	manual
Temperatur range	195° C / 380° F + moduls* 130°/ 160° / 215°
Operating pressure	-
Weight	1,15 kg / 2 1/2 lbs
Cable length	3 m / 10 ft

Subject to technical changes

* optionally available

Hotmelt glue



Diameter	Ø 43 mm
Material	SP = Sprayable hotmelt glue based on Polyolefin
	HM = Hotmelt glue based on Ethylen-Vinylacetat
	PA = Hotmelt glue based on Polyamid

Joh. Friedrich Behrens AG
Industrielle Befestigungssysteme
Bogenstraße 43 - 45
22926 Ahrensburg
Germany

Further information is available:
Tel: + 49(0) 41 02 78 - 444
Fax + 49 (0) 41 02 78 - 270
Email: info@bea-group.com
www.bea-group.com

BeA is member of the following associations:

